



```
read( did, options ) --> ( did-document, metadata )
```

```
resolve( did, options ) --> ( did-document, metadata )
```

```
dereference( did-url, options ) --> ( content, metadata )
```


dereference(did-url, options) --> (content, metadata)

did-url = did:example:1234 options = ()	content = DID document (default representation) metadata = DID document metadata (incl. MIME type)
did-url = did:example:1234 options = (no-cache=true)	content = DID document (default representation, not cached) metadata = DID document metadata (incl. MIME type)
did-url = did:example:1234 options = (result-type=<json or json-ld or cbor>)	content = DID document (requested representation) metadata = DID document metadata (incl. MIME type)
did-url = did:example:1234#key-1 options = ()	content = Part of DID document (default representation) metadata = DID document metadata
did-url = did:example:1234;version-time=1002034 options = ()	content = DID document (default representation, earlier version) metadata = DID document metadata
did-url = did:example:1234/my/path?testquery options = ()	content = Determined by DID method and/or by DID controller metadata = Determined by DID method and/or by DID controller
did-url = did:example:1234;service=agent/profile?query options = ()	content = (null) metadata = Selected service endpoint URL
did-url = did:example:1234;myparam=value options = ()	content = Determined by parameter extension spec metadata = Determined by parameter extension spec